

SILICONE E 400

SILICONE SPRAY, ANTIADHESIVE, SLIDING



Characteristics

Base:	Silicone oil with middle viscosity
Propellant:	Denatured and odourless hydrocarbons (VOC Free)
Appearance:	Transparent and colourless liquid
Colour:	Colourless
Odour:	Odourless
Temperature of Resistance:	From -40 to + 250 °C
It does not contain CFC	
It isn't toxic	

Description

SILICONE E 400 is used in the rubber and in the plastic materials industry, in the industrial bindery, typography, serigraphy, leather, tailoring.

It is a good mould releasing agent for plastic and rubber.

It lubricates the blades of the cutters for sheets of paper and polyethylene.

It is a good antistatic and sliding for working tables.

Instructions of use

Clean and degrease the mould or the surface before using the product.

Spray the products from 30 cm distance.

Packaging

Spray Aerosol ml 400

Box 25 Aerosol

Product Code 10510/04E

Head office and Production

Siliconi Commerciale® SpA
Via Francia 4
36053 Gambellara
Vicenza – ITALY
phone + 39.0444.649766
fax +39.0444.440018
e. mail: info@siliconi.it
www.siliconi.it

Production since 1957

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification.

The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.