

SILICONE SPRAY FOR WELDING

ANTISTATIC, ANTIADHESIVE, SLIDING SILICONE SPRAY



Characteristics

Base: Silicone oil at middle viscosity
Propellant: Denatured and odourless hydrocarbon
It does not contain CFC

Properties:

- It prevents the adhesion of the drosses
- It is a good antistatic

Description

SILICONE SPRAY is used in the rubber and in the welding industry.
It is used to prevent the adhesion of the drosses and the drops on the welding.
It is a good antistatic and sliding facilitating the sliding over the tables of work.
Treated pieces can't be over painted

Instructions of use

Before using the product clean and degrease the torch and the pieces to weld.
Spray the product from 30 cm distance.

Packaging

Spray Aerosol ml 500
Box 25 Aerosol
Product Code 10410/05SA

Head office and Production

Siliconi Commerciale® SpA
Via Francia 4
36053 Gambellara
Vicenza – ITALY
phone + 39.0444.649766
fax +39.0444.440018
e. mail: info@siliconi.it
www.siliconi.it

Production since 1957

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification.

The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.