

# OROSIL

## GOLD COLD WORK GALVANIZATION SPRAY



### Characteristics

Base: Pure zinc in synthetic vehicle  
 Aspect: Gold yellow clear  
 Propellant: Denatured and odourless butane (VOC Free)  
 Dry time: 5' about.  
 Purity of zinc powder: 98%  
 Resistance to corrosion: Very good (about 190 hours in salty fog)  
 Dry film thickness: 30/35 micron  
 CFC free

It does not contain chlorinated

### Properties:

- High gold-zinc content
- Fast drying
- High covering power
- It can be overpainted
- It doesn't drip
- High resistance to corrosion
- Good resistance to atmospheric agent, washing, oxidation of salty fog
- Colour similar to gold-galvanisation
- Long-time oxidation protection
- Perfect adhesion to the material

### Description

OROSIL is used for cold-work galvanize for yellow metal materials.

Zinc spray with high zinc content is particularly suitable for retouches in soldering, to restore or galvanize metal sheets, to galvanize and protect weather-exposed bolts for long periods, to restore the zinc film on gates, doors, metal sheets, tanks, metal structures.

It can be left as final finishing or it can be overpainted.

### Instructions of use

Clean and degrease the parts to treat.

Shake the can before using at least for one minute until the little ball inside the can is free to move. During the application shake the product in order to keep it homogeneous. Spray at 25 cm distance. After the use overturn the aerosol and spray the product few seconds to dodge the obstruction of the valve

Shelf life 1 year

### Packaging

Spray Aerosol ml 400  
 Box 12 Aerosol  
 Product Code 14110/04

---

### Head office and Production

Siliconi Commerciale® SpA  
 Via Francia 4  
 36053 Gambellara  
 Vicenza – ITALY  
 phone + 39.0444.649766  
 fax +39.0444.440018  
 e. mail: [info@siliconi.it](mailto:info@siliconi.it)  
[www.siliconi.it](http://www.siliconi.it)

### Production since 1957

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.